

AZUD HELIX 自清洗过滤系统400系列 AZUD HELIX AUTOMATIC 400 EQUIPMENT

在线过滤, 每组过滤单元由三个独立的滤头构成, 配有4"阀门。
最大流量: 1080 m³/h // 4752 gpm.

In-line or double equipment with groups of 3 independent filtering elements operated with 4" valves.
Maximum flow rate: 1080 m³/h // 4752 gpm.



SERIE 400 - L 型配置/ SERIES 400 - L Configuration

型号 Model	过滤单元数 x 尺寸 No. of Filters x Diameter	最大流量 Max. flow		管道尺寸 Manifold diameter	控制单元 Compatible control unit	
		m ³ /h	130 micron gpm		220 V AC	12 V DC
404/10FE	4X4"	360	1584	10" - 250	109T	209T
405/10FE	5X4"	450	1980	10" - 250		
406/10FE	6X4"	540	2376	10" - 250		
407/12FE	7X4"	630	2772	12" - 250		
408/12FE	8X4"	720	3168	12" - 300		
409/14FE	9X4"	810	3564	14" - 300		
410/14FE	10X4"	900	3960	14" - 300		
411/16FE	11X4"	990	4356	16" - 300		
412/16FE	12X4"	1080	4752	16" - 300	112	212P

SERIE 400 - D 型配置/ SERIES 400 - D Configuration

型号 Model	过滤单元数 x 尺寸 No. of Filters x Diameter	最大流量 Max. flow		管道尺寸 Manifold diameter	控制单元 Compatible control unit	
		m ³ /h	130 micron gpm		220 V AC	12 V DC
406/12FE	6X4"	540	2376	12" - 300	109T	209T
407/12FE	7X4"	630	2772	12" - 300		
408/12FE	8X4"	720	3168	12" - 300		
409/14FE	9X4"	810	3564	14" - 350		
410/14FE	10X4"	900	3960	14" - 350		
411/16FE	11X4"	990	4356	16" - 350		
412/16FE	12X4"	1080	4752	16" - 300		
					112	212P

标准过滤精度/ Standard filtration grades



叠片组/Discs

■ 400 micron. (40 mesh)
 ■ 200 micron. (75 mesh)
 ■ 130 micron. (120 mesh)
 ■ 100 micron. (150 mesh)